

Ergomat Sticky Mats provide a fast, convenient, reliable way to clean shoe soles or other items before entering a clean and sanitary area. Sticky Mats significantly reduce traffic-borne contaminants. Sticky Mats have proven themselves effective in a wide variety of industries such as microelectronics, aerospace, pharmaceuticals and food processing, the disposable Sticky Mat is the best, most reliable way to keep floors debris free.



Unmatched Features

- Each Sticky Mat consists of a stack of tear-off polyethylene films full adhesive sheets that effectively capture dirt and dust from foot-traffic and equipment wheels before they enter controlled environments.
- Each Sticky Mat is easily adhered to the floor or to a frame with double-faced adhesive tape.
- Sticky Mats utilize a water-based acrylic adhesive, which has a pH of 7-8 and doesn't contain benzoic acid.
- Certified by RoHS to be free from heavy metals and hazardous chemicals.

Dimensions & Quantities

- Sticky Mats are available in 18"x45" (46cm x 114cm) standard size white sheets (only) and includes 30 sheets/mat.
- Sticky mats are available in 10 mats/box.
- The laminate frame for the Sticky Mats is available in a 24"x51" (61cm x 129cm) size and standard colors; Grey-mix, Beige-mix, Blue-mix, Black-mix, Cappuccino-mix and Grey (plain).

The Sticky Mat Advantage

- This peel-off design eliminates messy and time-consuming cleaning and washing and makes it easy to keep a clean sticky mat at all times.
- A clear release sheet protects the top sheet of the sticky mat until it is ready to use.
- The corner tabs are consecutively numbered to show the number of remaining sheets, thereby helping you to keep track of the number of sheets remaining and preventing multiple sheets being removed at once.

ERGOMAT Sticky Mats Properties

Parameter	37 um (White)
Material	LDPE water-based adhesive (environmentally friendly)
Thickness	1.19mm
Structure	32 sheets per mat
Transparent Sheet Thickness (First & Last)	40 um/sheet
Other Sheets Thickness	37 um/sheet (other thickness can be customized)
Adhesive Force	400g/25mm +/- 10 (second to 31 st sheet adhesive force) 700g/25mm +/- 10 (bottom 31 st sheet adhesive force) (other adhesive force can be customized)
Dust Sticking Capacity	99.9% (five steps)
Temperature Resistance	60°C
Warranty Period	8 months

